



Paving Asphalt PG 64-22

ExxonMobil Asphalt , Canada

PERFORMANCE GRADED ASPHALT CEMENT

Product Description

Paving Asphalt PG 64-22 is a Performance Graded (PG) asphalt derived from specially selected crude oils via carefully controlled refining processes. The quality of ExxonMobil products is assured for every delivery. Products are manufactured according to global product integrity requirements.

Applications

Paving Asphalt PG 64-22 product is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before

Properties & Specifications

Paving Asphalt PG 64-22 product meets AASHTO M320 specification requirements:

| Asphalt Property | Units | Method | AASHTO M320 |
|---------------------------------|-------|-------------|-------------|
| Flash Point (C.O.C.) | °C | AASHTO T48 | 230 min |
| Apparent Viscosity at 135°C | Pa.s | AASHTO T316 | 3.00 max |
| Mass change, RTFO residue | mass% | AASHTO T240 | 1.00 max |
| DSRo (G*/sin δ) at 64°C | kPa | AASHTO T315 | 1.00 min |
| DSRr (G*/sin δ) at 64°C | kPa | AASHTO T315 | 2.20 min |
| DSRp (G*/sin δ) at 25°C | kPa | AASHTO T315 | 5000 max |
| BBR (Stiffness) at -12°C | MPa | AASHTO T313 | 300 max |
| BBR (m-value) at -12°C | - | AASHTO T313 | 0.300 min |

AASHTO M320 specifications may be subject to change.

Health & Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local representative or from www.imperial.com.

All trademarks used herein are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020

Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.imperial.com for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.



Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved