



MOBILGARD™ HSD CF-4

ExxonMobil Marine , 中国  
High Speed Diesel Engine Oil

Product Description

Mobilgard™ HSD CF-4 variants, 15W-40 and 20W-50 are diesel engines oils that provide proven protection of diesel engines operating in marine service applications. Mobilgard HSD CF-4 engine oils are recommended by ExxonMobil for use in a wide range of diesel engines for use in a variety of operating environments in various industries.

Features and Benefits

| Features                        | Advantages and Potential Benefits |
|---------------------------------|-----------------------------------|
| Thermal and oxidation stability | Controls sludge build-up          |
| TBN reserve                     | Deposit control                   |
| Component compatibility         | Long seal and gasket life         |

Applications

Mobilgard HSD CF-4 oils, 15W-40 and 20W-50 are designed to provide proven engine protection for marine diesel engines. Including those models typically used in industries such as inland, coastal, fishing, dredging, offshore service and other similar applications.

Specifications and Approvals

| This product is recommended for use in applications requiring: | MOBILGARD HSD 15W-40 CF-4 | MOBILGARD HSD 20W-50 CF-4 |
|----------------------------------------------------------------|---------------------------|---------------------------|
| API CF-4                                                       | X                         | X                         |

Properties and Specifications

| Property                                      | MOBILGARD HSD 15W-40 CF-4 | MOBILGARD HSD 20W-50 CF-4 |
|-----------------------------------------------|---------------------------|---------------------------|
| Grade                                         | SAE 15W-40                | SAE 20W-50                |
| Ash, Sulfated, mass%, ASTM D874               | 0.73                      | 0.72                      |
| Density @ 15 C, kg/l, ASTM D4052              | 0.88                      | 0.88                      |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 232                       | 231                       |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 14                        | 18.2                      |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 104                       | 162.9                     |
| Pour Point, °C, ASTM D97                      | -39                       | -30                       |
| Total Base Number, mgKOH/g, ASTM D2896        | 6                         | 6.4                       |
| Viscosity Index, ASTM D2270                   | 136                       | 124                       |

**Health and Safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

ExxonMobil Marine Limited

Ermyn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary slightly.

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All  
Rights Reserved