ExxonMobil

Flexxipave I-D

ExxonMobil Specialties , 中国

Flexxipave I-D is a polymer modified asphalt

Product Description

Flexxipave I-D is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Application

Flexxipave I-D is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties and Specifications

Property	Min	Max
Penetration, 25C, 100g, 5s, 0.1mm, T0604	40	60
Softening Point, R&B, °C, T0606	60	
Ductility @5C, 5cm/min, cm, T0605	20	
Flash Point, °C, T0611	230	
Elastic Recovery, 25C, %, T0662	75	
Retained penetration ratio on RTFOT(T0610) Residue, 25C, %, T0604	65	
Ductility @5C on RTFOT(T0610) Residue, cm, T0605	15	

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020
ExxonMobil Asia Pacific Ltd
1 HarbourFront Place
#06-00 HarbourFront Tower One
Singapore 098633

+65 6885 5000
http://www.exxonmobil.com

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved