Mobilgard DEO Series Page 1 of 2

# **E**xonMobil

## Mobilgard DEO Series

ExxonMobil Marine , Indonesia

High Speed Diesel Engine Oil

#### **Product Description**

Mobilgard  $^{\text{TM}}$  DEO ( Diesel Engine Oil) Series are high performance monograde diesel engine oils formulated with high quality base stocks and a balanced additive  $^{\text{SM}}$  for use in marine applications.

#### Features and Benefits

| Features   | Advantages and Potential Benefits  |
|--|--|
| Extended TBN reserve                                       | Protects engine parts from corrosive wear and deposits Controls formation of acids when using higher fuels |
| Good protection against oil thickening and sludge built-up | Prolonged engine life  |
| Excellent thermal and oxidation stability                  | Keeps engines clean and operating smoothly   |
| Increased high temp/high shear performance                 | Reduced engine scuffing, bore polishing and ring sticking  |

## **Applications**

Mobilgard DEO Series are designed to provide superior performance in severe marine applications, especially for older and reconditioned marine high speed engines. Mobilgard ™ DEO Series are used in engines where a monograde lubricant is recommended requiring API CF or CD.

## Specifications and Approvals

| This product is recommended for use in applications requiring: | MOBILGARD DEO 30 | MOBILGARD DEO 40 |
|--|------------------|------------------|
| API CD   | Х                | X                |
| API CF   | X                | X                |

#### Properties and Specifications

| Property                                      | MOBILGARD DEO 30 | MOBILGARD DEO 40 |
|---|------------------|------------------|
| Grade   | SAE 30           | SAE 40           |
| Ash, Sulfated, mass%, ASTM D874               | 1.1              | 1.1              |
| Density @ 15 C, g/cm3, ASTM D4052             | 0.89             | 0.9              |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 256              | 254              |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 11.8             | 14.6             |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 106              | 146              |

Mobilgard DEO Series Page 2 of 2

| Property                               | MOBILGARD DEO 30 | MOBILGARD DEO 40 |
|--|------------------|------------------|
| Pour Point, °C, ASTM D97               | -21              | -21              |
| Total Base Number, mgKOH/g, ASTM D2896 | 10.1             | 10.1             |
| Viscosity Index, ASTM D2270            | 99               | 99               |

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020 ExxonMobil Marine Limited Ermyn Way Leatherhead, Surrey United Kingdom KT22 8UX

http://www.exxonmobil.com

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly

