ExonMobil

MOBILGARD™ HSD 20W-50 CI-4

ExxonMobil Marine, Sri Lanka

High Performance Diesel Engine Oil

Product Description

Mobilgard HSD 20W-50 CI-4 by ExxonMobil is an extra high performance, multi-grade engine oil specifically formulated for severe service high-speed diesel eng marine applications. Its advanced chemistry provides outstanding performance in both modern, demanding low-emission diesel engines and older diesel e operating on low or high sulphur distillate fuel.

Features and Benefits

Mobilgard HSD 20W-50 CI-4 combines a blend of high quality base stocks with an excellent balanced additive system to help provide exceptional control of oil thic due to soot build-up and high temperatures, as well as outstanding resistance to oxidation, corrosion, and high temperature varnish deposits.

When used as recommended by ExxonMobil, Mobilgard HSD 20W-50 Cl-4 diesel engine oil provides the following features and potential benefits:

| Features |
|---|
| Outstanding thermal and oxidation stability |
| Excellent wear protection |
| High Viscosity Index |
| Increased high temp/high shear performance |
| Outstanding TBN retention |
| Excellent water tolerance and separation capability |
| Excellent low temperature properties |

Applications

Mobilgard HSD 20W-50 CI-4 is designed to provide outstanding performance in some of the most severe service marine applications of high-speed diesel engine: as Mercedes Benz.

Specifications and Approvals

| This product has the following approvals: |
|--|
| MB-Approval 228.3 |
| |
| This product meets or exceeds the requirements of: |

Properties and Specifications

API CI-4

| Property | |
|----------|--|
| | |

| Property | |
|---|------------|
| Grade | SAE 20W-50 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 163 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10.2 |
| Viscosity Index, ASTM D2270 | 132 |
| Ash, Sulfated, mass%, ASTM D874 | 1.1 |
| Pour Point, °C, ASTM D97 | -26 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.88 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 18.9 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2023

