



PAVING ASPHALT 60/70 TPI

ExxonMobil Asphalt , Malaysia

PENETRATION GRADED ASPHALT PRODUCT

Product Description

Paving Asphalt 60/70 TPI is a penetration graded asphalt product. The specifications apply to those asphalt acquired for resale by ExxonMobil through purch exchange from third Party supplier.

Applications

Paving Asphalt 60/70 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties and Specifications

| Property                             | Standard Method(a) | Limit   |       |
|--------------------------------------|--------------------|---------|-------|
| Penetration, 25 C, 0.1 mm            | ASTM D5            | Min-Max | 60-80 |
| Softening Point, °C                  | ASTM D36           | Min     | 46    |
| Flash Point, Cleveland Open Cup, °C  | ASTM D92           | Min     | 232   |
| Solubility in Trichloroethylene, wt% | ASTM D2042         | Min     | 99.0  |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

ExxonMobil

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved

