



Industrial Bitumen OX

ExxonMobil Asphalt , Netherlands

OXIDISED BITUMEN PRODUCT

Product description

Industrial Bitumen OX products are derived from specially selected crude oils via carefully controlled refining processes.

The quality of ExxonMobil products is assured for every delivery. They are produced and controlled according to the ExxonMobil Global Product Integrity Management System, EN ISO 9000 or equivalent standard.

Applications

Users should conduct appropriate testing before use of Industrial Bitumen OX grades for specific applications.

Properties and Specifications

Industrial Bitumen OX grades meet the following specification requirements:

Property	Unit	Test Method	INDUSTRIAL BITUMEN OX 85/25	INDUSTRIAL BITUMEN OX 95/40
Softening point in glycerol	°C	EN 1427	80/90	90/100
Penetration at 25°C	0.1 mm	EN 1426	20/30	35/45
Flash point (COC) (min)	°C	EN ISO 2592	250	250
Solubility in toluene (min)	% (m/m)	EN 12592	99	99
Specific gravity at 25°C		EN 15326	1.00/1.10	1.00/1.10
Loss on heating at 163°C (max)	% (m/m)	EN 13303	0.5	0.5

Above specifications may be subject to change.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.exxonmobil.com for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved