



Marcol 82

ExxonMobil Specialties , Slovenia

Medicinal grade White Oil

Product Description

Marcol 82 is a purified mixture of liquid saturated hydrocarbons. It is a colourless, transparent oily liquid and is essentially odourless and tasteless. It is obtained from petroleum through several refining stages, including an ultimate purification by catalytic hydrogenation.

Marcol 82 is manufactured to exceed the purity requirements of the Pharmacopoeias. Due to its superior chemical inertness, it demonstrates better colour and oxidation stability than most mineral and vegetable oils, when stored and used under controlled conditions.

ExxonMobil White Oils are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

CAS number: 8042-47-5

EINECS number: 232-455-8

INCI name (Europe): Paraffinum Liquidum

CTFA Dictionary name (USA): Mineral Oil

Applications

Marcol 82 can be used in a variety of food-contact, cosmetic and pharmaceutical applications (*), subject to the applicable laws and regulations in each country (**)

(*) To limit ingestion and aspiration hazards, Marcol 82 should not be used in nasal, oral or lip care products or as a food additive other than for food contact materials

(**) User must check compliance with applicable regulations

COSMETICS

Marcol 82 is widely used as a component of a great variety of cosmetic products:

- Emollients and moisturisers (cleansing oils and milks, body lotions and creams, suntan lotions and milk, make-up powders)
- Baby products (shampoos, baby oils, bath oils)
- Hair care products (hot oil treatments, gels, scalp pomades)
- Neutral and protective diluents for other cosmetic ingredients such as essential oils
- Other applications such as bath cubes, anti-perspirant and deodorant sticks.

Marcol 82 provides many practical advantages to the formulation specialist:

- Excellent skin compatibility, very low irritancy and no comedogenicity
- Very good balance between resistance to bacteria and final biodegradability, with minimal environmental impact.

PHARMACEUTICALS

Marcol 82 offers a high level of safety, thanks to its high purity (absence of toxic polycyclic aromatics, heavy metals), the complete destruction of germs in the high temperature manufacturing process, and specific packaging and handling procedures.

Marcol 82 is an ingredient of pharmaceutical topical ointments and petroleum jellies. It can be used as a pelletiser aid, and in the manufacture of gelatine capsules.

Regulations and Claims

This product is registered to the requirements of:
NSF H1

This product meets or exceeds the requirements of:
FDA21 CFR 178.3620(a)
US Pharmacopeia/National Formulary Light Mineral Oil monograph
European Pharmacopoeia Light Liquid Paraffin monograph

Properties and Specifications

Property	Standard Method(a)	Typical	Min	Max
Appearance	Visual		Clear and Bright	
Odor	OLFACTORY		odorless or almost odorless	
Color, Saybolt	ASTM D6045		+30	
Kinematic Viscosity @ 40 C, mm2/s	ASTM D445		14.5	17.5
Kinematic Viscosity @ 100 C, mm2/s	ASTM D445	3.6		
Dynamic Viscosity @ 20 C, mPa.s	CALCULATED		27	37
Density @ 15 C, kg/m3	ASTM D4052		845	858
Relative Density @ 20 C/20 C	ASTM D4052		0.843	0.851
Relative Density @ 25 C/25 C	ASTM D4052		0.841	0.851
Pour Point, °C	ASTM D5950			-6
Flash Point, Cleveland Open Cup, °C	ASTM D92		182	
Refractive Index, 20 C	ASTM D1218		1.464	1.471
Paraffinic Carbons (Cp), %	AM-S 1805	65		
Naphthenic Carbons (Cn), %	AM-S 1805	35		
Aromatic Carbons (Ca), %	AM-S 1805	0		

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

ExxonMobil Lubricants & Specialties Europe
Hermeslaan 2
1831 Machelen
BELGIUM
+32-2-722-2111
<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved