



Prowax 750

ExxonMobil Specialties, Slovenia

Product Description

Prowax 750 is a mid-to-high range melting point product in the Prowax line of petroleum slack and scale waxes. It is a translucent crystalline material in the solid state and an amber-to-brown, clear liquid when molten. It is derived from petroleum via a carefully controlled refining process. Prowax 750 is comprised of a mixture of straight chain normal paraffin and branched, iso-paraffin hydrocarbons.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Prowax 750 can be used in the following applications subject to applicable laws and regulations in each jurisdiction*:

- Wax emulsions
- Wax isomerisation feedstock
- Wax blends

* User must check compliance with applicable regulations

Properties and Specifications

Property	Standard Method(a)	Typical	Min	Max
Congealing Point, °C (°F)	ASTM D 938		58.0(136.4)	68.0(154.4)
Oil Content, wt %	ASTM D 3235			35.0
Kinematic Viscosity @ 100°C, mm ² /s (cSt)	ASTM D 445		7.0	9.0
Density, @ 15°C (59°F), kg/m ³ (b)	ASTM D 1298	854		
Flash Point COC, °C (°F)	ASTM D 92		220(428)	

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

(b) Density at 15°C is based on measurement of the wax liquid density at a higher temperature corrected to 15°C using ASTM D1250 Table B.

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

Health and Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com

The ExxonMobil logotype (and any other trademarks) are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

06-2020

ExxonMobil Lubricants & Specialties Europe

Hermeslaan 2

1831 Machelen

BELGIUM

+32-2-722-2111

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved