



Mobil Delvac 1340 F2

Mobil Commercial Vehicle Lube , Argentina

High Performance Diesel Engine Oil

Product Description

Mobil Delvac 1340 F2 is a high performance monograde diesel engine oil formulated from advanced technology base oils and a balanced additive system. It is specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Also used in some commercial vehicles manual transmissions.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life, Less wear, Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control, Controls formation of acids when using higher sulfur fuels

Applications

Recommended by ExxonMobil for use in:

Naturally aspirated and turbo-charged diesel powered equipment

On highway light and heavy duty trucking

Off highway industries including: construction, mining, quarrying, and agriculture

Commercial vehicles manual transmissions according to MB-Approval 235.12

Specifications and Approvals

This product has the following approvals:
MB-Approval 235.12

This product is recommended for use in applications requiring:
API CF
API SF

Properties and Specifications

Property	
Grade	SAE 40
Appearance, AMS 1738	Clear and Bright

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	264
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.7
Viscosity Index, ASTM D2270	100
Total Base Number, mgKOH/g, ASTM D2896	10
Pour Point, °C, ASTM D97	-30

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Esso Petrolera Argentina SRL.

Carlos Maria della Paolera 299, Capital Federal, Argentina

0800- 888088

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved