



Mobilfluid™ 125

Mobil Industrial , Austria

Extra High Performance Power Transmission Fluid

Product Description

Mobilfluid 125 is an extra high performance power transmission fluid that is formulated for use in hydrodynamic gears and hydraulic systems typically found in marine, construction, and industrial applications. It is formulated using high performance basestocks and advanced additives to deliver the precise performance required to transfer power responsively. Mobilfluid 125 is engineered to withstand the stresses of heavy-duty, low and high speed applications in a wide range of severe operating environments.

Features and Benefits

The use of hydrodynamic gear systems and hydraulic control systems depends on high performance fluids to achieve consistent and responsive control and efficient operation of the equipment. These systems operate under high pressures and temperatures that can cause deposits in control valves where precise control of torque converter hydraulics takes place. The key benefits of Mobilfluid 125 include:

| Features | Advantages and Potential Benefits |
|---|---|
| Good wear protection | Extended component life, increased productivity, and lower maintenance costs |
| Effective resistance to thermal degradation and oxidation | Significant reduction in harmful lacquers, deposits, and sludge Maintains power transfer and good control response Extends oil service life |
| Good low temperature properties | Easy start-up and responsive hydraulic control |
| Effective rust and corrosion protection including long stoppages in wet or humid ambient conditions | Reduces wear with reliable equipment start-up and lower maintenance costs |
| Excellent air release properties eliminate foaming problems | Delivers optimal hydraulic response and power transfer Maintains fluid film for improved lubrication |
| Compatible with seals and gasket materials used in these systems | Reduced fluid leakage, pressure losses, and contamination |

Applications

Recommended by ExxonMobil for use in:

- Fluid couplings and drives, torque converters, and hydraulic control systems used in railroad, marine, construction, and industrial applications

Specifications and Approvals

| |
|---|
| This product has the following approvals: |
| Voith Turbo 120.00059010 |

Properties and Specifications

| Property | |
|----------|--|
|----------|--|

| Property | |
|---|--------|
| Grade | ISO 32 |
| Density @ 15 C, g/cm3, ASTM D4052 | 0.878 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 225 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 5.3 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 30 |
| Pour Point, °C, ASTM D97 | -30 |
| Viscosity Index, ASTM D2270 | 104 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTOMOBIL

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved