



Mobil Super 3000 Formula G 5W-30

Mobil Passenger Vehicle Lube , Austria

High Performance Motor Oil

Product Description

Mobil Super 3000 Formula G 5W-30 is a low ash high performance motor oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

Mobil Super 3000 Formula G 5W-30 offers excellent performances at both low and high operating temperatures and long term engine protection. Key features and benefits include:

- Helps maintain efficiency of Diesel particulate filters and gasoline catalytic convertors
- Protects engines from wear and deposit build-up
- Helps fuel economy through reduced friction
- Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles

Applications

dexos2™ is required for all 2010 new GM/Opel/Vauxhall/Chevrolet Diesel and Gasoline models. GM/Opel have advised that dexos2™ specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet Diesel and Gasoline vehicles can use dexos2™ lubricants.

Specifications and Approvals

This product has the following builder approvals:

GM dexos2

This product is approved by the following OEMs:

VW505 00

VW505 01

This product is of quality level, but not approved:

GM-LL-A-025

GM-LL-B-025

This product meets or exceeds the requirements of the following industry specification:

ACEA C3

This product meets or exceeds the requirements of the following industry specification:

APISL

APISM

APISN

Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	68
Phosphorus, mass%, ASTM D4951	0.08
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved