



Mobil Super Moto™ 10W-30

Mobil Passenger Vehicle Lube , Australia

Premium Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto™ 10W-30 is high performance engine oil for modern motorcycle engines. Though developed for latest engine technology, Mobil Super Moto 10W-30 provides good protection for old technology engine too, align with motorcycle engine technology development trends led by major OEMs. Instant engine protection from heat-activated anti-wear molecule™ can make engine protected from the start of the engine to the high temperature conditions caused by long, continuous driving.

Features and Benefits

Mobil Super Moto 10W-30 is made of highly refined, quality mineral oils and an advanced additive system.

Balanced quality oil and additives enables keep engine clean without corrosion, protecting engine and gearbox in one circulation system.

Hi traction of Mobil Super Moto 10W-30 prevents clutch slippage.

Instant engine protection from heat-activated anti-wear molecule.

57% more wear protection against industry standard based on Industry standard engine test Sequence IVA in API SL

Applications

Best for the modern four-stroke motorcycle engines JASO MA or JASO MA2 recommended by OEMs.

Good protection to motorcycle engines before introduction of JASO MA or JASO MA2.

Specifications and Approvals

This product meets or exceeds the requirements of the following industry specification:	
JASO MA	
JASO MA2	
JASO MA	
JASO MA2	
API SL	

Properties and Specifications

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.5
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	71

Property	
Viscosity Index, ASTM D2270	140
Density @ 15 C, g/ml, ASTM D4052	0.880
Pour Point, °C, ASTM D97	-25
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	5.5
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	20000
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.2

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2020

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved