



Mobil Formula S 5W-30

Mobil Passenger Vehicle Lube , Australia

Product Description

Mobil Formula S 5W-30 is a premium semi-synthetic engine.

Features and Benefits

Mobil Formula S 5W-30 provides

- Excellent fuel economy
- Outstanding wear protection
- Excellent engine cleanliness
- High temperature protection

Applications

Mobil Formula S 5W-30 is suitable for use in gasoline and LPG powered vehicles. It is ideally suited for normal to occasionally severe operating conditions and highway cruising.

Specifications and Approvals

Mobil Formula S 5W-30 meets or exceeds the requirements of:	
API	SN/SM
ILSAC	GF-5
Ford	WSS-M2C929-A
Ford	WSS-M2C946-A

Mobil Formula S 5W-30 is also recommended by ExxonMobil for use in applications requiring:	
API	CF
ILSAC	GF-4
GM	6094M
GM	9986231
Ford	WSS-M2C915-A

Typical Properties

Mobil Formula S 5W-30	
SAE Grade	5W-30
Viscosity, ASTM D 445	
cSt @ 40° C	62
cSt @ 100° C	10.6

Mobil Formula S 5W-30	
Viscosity Index, ASTM D 2270	162
Sulfated Ash, wt%, ASTM D 874	0.8
HTHS Viscosity, mPa·s @ 150° C, ASTM D4683	3.2
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	225
Density @15° C kg/l, ASTM D 4052	0.86

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Formula S are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved