



Mobil Super™ 3000 Formula V 5W-30

Mobil Passenger Vehicle Lube , Bulgaria

High Performance Engine Oil

Product Description

Mobil Super™ 3000 Formula V 5W-30 is a low SAPS (or low ash) high performance engine oil designed to meet the demanding requirements of extended service life whilst still contributing towards fuel economy and superior engine cleanliness in modern gasoline and diesel engines designed by German builders.

Features and Benefits

Mobil Super 3000 Formula V 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

- Extended service interval as per VW, MB, BMW requirements.
- Full compatibility with most Particulate Filters and Catalytic Convertors.
- Helping achieve fuel economy (as per ACEA C3).
- Improved engine internal cleanliness to maintain engine efficiency over life of vehicle.
- Fast oil circulation and protection.

Applications

Mobil Super 3000 Formula V 5W-30 has been designed to meet the requirements of modern (Euro 6 or prior) turbo injection diesel and gasoline engines equipped with particle filters or catalytic converters. It is particularly designed for the needs of the VW Audi group where extended drain is achieved in conjunction with electronic service indicators. The oil is also recommended for many BMW and MB passenger vehicles.

Specifications and Approvals

| This product has the following approvals: |
|--|
| VW 507 00 |
| VW 504 00 |
| MB-Approval 229.51 |
| MB-Approval 229.31 |
| Porsche C30 |
| BMW Longlife 04 |

This product meets or exceeds the requirements of:

ACEA C3

API SN

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-30 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 65.5 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 11.65 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 236 |
| Density @ 15 C, g/ml, ASTM D1298 | 0.852 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |
| Phosphorus, mass%, ASTM D4951 | 0.08 |
| Pour Point, °C, ASTM D97 | -45 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.


09-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved