



FAXAM™ 32

Mobil Industrial , Byelorussia

Paraffinic Process and Flushing Oil

Product Description

FAXAM™ 32 is paraffinic process oil that can be used in a wide variety of industrial and process oil applications. FAXAM 32 can be used as a lubricant in non-critical applications, where oil operating conditions are moderate and there are no requirements for anti-wear or extreme pressure additives. As process oils, their physical characteristics make them suitable for use as a diluent or carrier oil in the manufacture of products such as lubricating oil additives, paper defoamants, seals, carbon paper, and other chemical formulations. FAXAM 32 can be used as a flushing oil for cleaning lubrication systems.

Features and Benefits

- light colour
- low odour
- good solubility characteristics
- good low temperature properties

Applications

- As a flushing oil in circulating systems
- As a carrier oil in formulations requiring good solvency
- As lubricant in less critical systems, where operating conditions are moderate and anti-wear and extreme pressure additives are not required.

Typical Properties

FAXAM	32
ISO Viscosity Grade	32
Colour, ASTM D1500	1.0
Kinematic Viscosity @40°C, ASTM D445	32
Viscosity Index, ASTM D2270	100
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-12

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect

product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved