



Mobil Super™ 3000 5W-30

Mobil Passenger Vehicle Lube , Brazil

Synthetic Motor Oil for Diesel Engines

Product Description

Mobil Super™ 3000 is a synthetic motor oil, which provides excellent high temperature protection even under severe operating conditions. Mobil Super 3000 is designed to help provide long engine life and outstanding protection in vehicles of all ages. Mobil Super 3000 provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super 3000 5W-30 is recommended by ExxonMobil for use in applications requiring API CF and also meets or exceeds the requirements of API SN.

Features and Potential Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection to help keep engines cool
- Permits extended operation at elevated temperatures (up to 400° F) without oxidative oil thickening and oil breakdown
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts

Applications

- Mobil Super 3000 5W-30 is recommended for diesel fueled automobiles where a 5W-30 viscosity is required.

Specifications and Approvals

Mobil Super 3000 meets or exceeds the requirements of:	5W-30
API SN	X

Mobil Super 3000 is also recommended by ExxonMobil for use in applications requiring:	5W-30
API CF	X

Typical Properties

Mobil Super 3000	5W-30
Density @15°C, kg/l	0.850
Viscosity @ 100°C, cSt	10.3
CCS @-30°C , cP	3670
MRV @-35°C, cP	9300

Mobil Super 3000	5W-30
Viscosity Index	168
Pour Point, °C	-36
Flash Point, °C,ASTM D 92	212

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

Esso Brasileira de Petróleo Ltda.
Rua Victor Civita, 77, Bloco 1
22775-044 Rio de Janeiro-RJ-BRASIL

5521 3433-2000

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved