



Mobil Delvac 1™ 5W-40

Mobil Commercial Vehicle Lube , Belarus

High Performance Heavy Duty Diesel Engine Oil

Product Description

Mobil Delvac 1 5W-40 is a fully synthetic high performance heavy duty diesel engine oil that helps towards long engine life while providing long drain capability for modern diesel engines operating in severe applications. Mobil Delvac 1 5W-40 delivers excellent performance in modern low emission engines, including refrigerated units, as well as older, well-maintained engines. Mobil Delvac 1 5W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found in the on-road transport and off-road mining, construction, and agricultural industries. Mobil Delvac 1 also meets the requirements of the API SL specification for gasoline engines used in mixed fleets.

The excellent performance of Mobil Delvac 1 5W-40 is the result of extensive cooperative development work with major equipment builders and application of advanced lubrication technology. As a result, this product meets or exceeds the requirements of some of the latest API, ACEA, JASO, and Global industry specifications for diesel engine oils, as well as the requirements of many major American, European, and Japanese engine manufacturers.

Features and Benefits

Many modern, low emission diesel engines generate more soot and operate at higher temperatures than older engines. This significantly increases the need for high performance lubricants. Current tighter engine designs reduce oil consumption, resulting in less fresh oil makeup to replenish depleted additives. Top piston rings are located higher, bringing the oil film closer to the combustion chamber and exposing the lubricant to severe thermal stresses. Mobil Delvac 1 5W-40 maintains outstanding performance at high temperatures. It is also fully compatible with conventional oils. The key benefits include:

1 Relative to conventional 15W-40 engine oil. Actual fuel economy improvement is dependent on vehicle/equipment type, outside temperature, driving conditions and your current fluid viscosity

| Features | Advantages and Potential Benefits |
|---|--|
| Meets or exceeds demanding specifications of major OEMs | One engine oil for mixed fleet operations |
| Outstanding thermal and oxidation stability | Control of low temperature sludge build-up and high temperature deposits |
| Low volatility, excellent wear and bore polish control | Good oil consumption control |
| Expertly formulated low viscosity formulation | Fuel economy potential(1) |
| Exceptional low temperature pumpability | Easier engine start-up and reduced wear |
| Good resistance to corrosion | Helps towards long life of critical wear surfaces |
| Long drain capability | Help towards operational efficiency and overall cost control |
| Component compatibility | Long gasket and seal life, extended service intervals |

Applications

Mobil Delvac 1 5W-40 is recommended for use in super high performance diesel applications, including modern low emission engine designs with Exhaust Gas Recirculation (EGR). These applications include the following:

- On-highway engines operating in both high speed/high load and stop-and-go conditions
- Off-highway engines operating in severe low speed/heavy load conditions
- Virtually all diesel powered equipment from American, European, and Japanese equipment builders

- Refrigeration units

Specifications and Approvals

This product has the following approvals:

Detroit Fluids Specification 93K214

MB-Approval 228.5

VOLVO VDS-2

This product is recommended for use in applications requiring:

API CG-4

API CF-4

API CF

CATERPILLAR ECF-1-a

Cummins CES 20072

Cummins CES 20071

CUMMINS CES 20075

This product meets or exceeds the requirements of:

API CI-4 PLUS

API CI-4

API CH-4

API SL

API SJ

Cummins CES 20078

Cummins CES 20077

Cummins CES 20076

Ford WSS-M2C171-D

GLOBAL DHD-1

RENAULT TRUCKS RXD

ACEA E4

ACEA E7

This product meets or exceeds the requirements of:

VOLVO VDS-3

RENAULT TRUCKS RLD-2

Mack EO-N

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-40 |
| Ash, Sulfated, mass%, ASTM D874 | 1.35 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.854 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 226 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.8 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 102 |
| Pour Point, °C, ASTM D97 | -45 |
| Total Base Number, mgKOH/g, ASTM D2896 | 12 |
| Viscosity Index, ASTM D2270 | 151 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved