



Mobil Delvac MX OE 20W-50

Mobil Commercial Vehicle Lube , 中国

Extra High Performance Diesel Engine Oil

Product Description

Mobil Delvac MX OE 20W-50 is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

Features and Benefits

Mobil Delvac MX OE 20W-50 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

| Features | Advantages and Potential Benefits |
|--|--|
| High thermal and oxidation stability | Reduced sludge build-up, deposits and viscosity increase |
| TBN reserves | Deposit control and acid neutralisation |
| Stay-in-grade shear stability | Wear protection and viscosity control |
| Advanced detergency/dispersancy | Cleaner engines and longer component life |
| Improved soot handling | Improved viscosity control and used oil pumpability |
| Excellent low temperature properties | Start-up wear protection |
| Component compatibility | Longer gasket and seal life |
| Meets demanding specifications of key OEMs | One engine oil for mixed fleet operations |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Mixed fleet applications

Specifications and Approvals

| | |
|--|---|
| Mobil Delvac MX OE 20W-50 meets or exceeds the requirements of the following industry specification: | |
| API CI-4 | X |
| Mobil Delvac MX OE 20W-50 has the following builder approvals: | |
| MB-Approval 228.3 | X |

Typical Properties

| | |
|--------------------------------------|--------|
| Mobil Delvac MX OE 20W-50 | |
| SAE Grade | 20W-50 |
| Viscosity, ASTM D 445 | |
| cSt @ 40°C | 162 |
| cSt @ 100°C | 18.9 |
| Viscosity Index, ASTM D 2270 | 132 |
| Sulfated Ash, wt%, ASTM D 874 | 1.1 |
| Total Base # , mg KOH/g, ASTM D 2896 | 10 |
| Pour Point, °C, ASTM D 97 | -27 |
| Flash Point, °C, ASTM D 92 | 235 |
| Density @ 15°C kg/l, ASTM D 4052 | 0.89 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube XHP are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved