Mobil 1™ ESP X2 0W-20 Page 1 of 2



Mobil 1™ ESP X2 0W-20

Mobil Passenger Vehicle Lube, Dominican Republic

Advanced Fuel Economy, Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ ESP x2 0W-20 is an advanced full synthetic motor oil specifically designed to provide outstanding engine cleanliness, wear protection, strong durability and advanced fuel economy* to keep your engine running like new. Mobil 1 ESP x2 0W-20 is our latest technology combining durability and protection with a low viscosity, low friction engine oil that was designed in cooperation with key European Original Equipment Manufacturers (OEMs). Mobil 1 ESP x2 0W-20 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in new emerging diesel and gasoline powered European vehicles that require SAE 0W-20 viscosity grades.

*compared vs Mobil 1 ESP Formula 5W-30.

Applications

Mobil 1 ESP x2 0W-20 is recommended for the new high-performance gasoline and diesel engines found in emerging European vehicles that require SAE 0W-20 viscosity grades.

- Mobil 1 ESP x2 0W-20 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.
- ****Always consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and specifications.

Specifications and Approvals

| his product has the following approvals: |
|--|
| GM dexosD Licensed |
| ИВ-Approval 229.71 |
| Porsche C20 |
| TJLR.03.5006 |
| TJLR.51.5122 |
| /W 508 00 |
| /W 509 00 |

| This product meets or exceeds the requirements of: |
|--|
| API SL |
| API SN Engine Test Requirements |
| API SN PLUS ENGINE TEST REQUIREMENTS |

Mobil 1™ ESP X2 0W-20 Page 2 of 2

| This product meets or exceeds the requirements of: |
|--|
| API SP ENGINE TEST REQUIREMENTS |
| ACEA C5 |

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 0W-20 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 |
| Density @ 15.6 C, g/cm3, ASTM D4052 | 0.842 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 7.9 |
| Pour Point, °C, ASTM D97 | -51 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

