



Mobil ATF™ 200

Mobil Passenger Vehicle Lube , Finland

Automatic Transmission Fluid

Product Description

Mobil ATF™ 200 is formulated to function as a power transmission fluid in torque converters, a hydraulic fluid in control and servo systems, a lubricant for bearings and gears, a friction controlling medium for the bands and clutches and a heat transfer medium to carry heat generated in transmissions to the gear case or oil cooler.

Due to its high Viscosity Index Mobil ATF 200 undergoes relatively small changes in fluidity regardless of operating or ambient temperatures. This ensures excellent performance as a hydraulic medium giving good operation under high temperature conditions and minimum power losses under cold conditions. control system.

Features and Benefits

Mobil ATF 200 offers the following benefits:

- Correct frictional characteristics give smooth transmission and perfect synchronisation, over a long period under continual severe operating conditions
- Protection against deposit formation and evaporation losses at high operating temperatures with very good low temperature operation
- Good protection against wear, resistance to rust, corrosion and foam
- Compatible with seal materials used in transmission units
- Low maintenance costs, and good operating profits

Specifications and Approvals

This product has the following approvals:

MB-Approval 236.2

This product is recommended for use in applications requiring:

GM Type A Suffix A

Properties and Specifications

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	>190
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	40
Viscosity Index, ASTM D2270	153
Color, Visual	Red

Property	
Pour Point, °C, ASTM D97	-39
Specific Gravity, 15 C/15 C, ASTM D4052	0.88

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

ExxonMobil Finland Oy Ab
Satamatie 10
21100 Naantali - FINLAND

+358 (0) 10 40 8500

<http://www.mobil.fi>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO
2012 1

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved