



Mobil Super 3000 XE1 5W-30

Mobil Passenger Vehicle Lube , Croatia

Synthetic Engine Oil

Product Description

MOBIL SUPER™ 3000 XE1 5W-30 is a synthetic high-performance low ash engine oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

Mobil Super 3000 XE1 5W-30 helps maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and gasoline vehicles. It permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown. The product provides excellent fluidity at low temperatures and rapid oil circulation around the engine.

Features
Helps maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and gasoline vehicles.
Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
Provides excellent fluidity at low temperatures and rapid oil circulation around the engine.

Applications

Mobil Super 3000 XE1 5W-30 is developed to meet the latest specifications for engine oils and is compatible with the latest Diesel Particulate Filters and all gasoline catalytic converters. It offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge and deposit build-up. It is the recommended product to use in BMW vehicles requiring BMW LL-04 specification.

Specifications and Approvals

This product has the following approvals:
BMW Longlife 04
MB-Approval 229.31
MB-Approval 229.51
MB-Approval 229.52

This product meets or exceeds the requirements of:
API SL
API SM
API SN

This product meets or exceeds the requirements of:

API SN PLUS

ACEA C3

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	69.2
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12
Phosphorus, mass%, ASTM D4951	0.08
Density @ 15 C, g/cm ³ , ASTM D4052	0.85
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Ash, Sulfated, mass%, ASTM D874	0.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved