



## Mobil Coolant Ready Mixed -36°C

Mobil Ancillary , Indonesia

High Performance Coolant

### Product Description

Mobil Coolant ready mixed is a high performance coolant designed to provide efficient protection down to -36°C during winter condition. It is a ready to use product has been premixed with 50% Mobil Antifreeze and 50% water.

### Features and Benefits

Mobil Coolant ready mixed contains mono ethylene glycol and helps to prevent winter freezing and summer overheating over a 2 years period. It also provides very protection against corrosion

### Applications

Mobil coolant ready mixed is recommended by ExxonMobil for use in applications requiring BS6580-1992 quality standard. Mobil Coolant Ready Mixed should not be mixed with other engine coolants. Most coolant blends are based on carefully balanced mixtures of various corrosion inhibitors. Mixing of coolants with different packages can lead to loss of corrosion protection.

### Specifications and Approvals

Mobil Coolant Ready Mixed is recommended by ExxonMobil for use in applications requiring the following industry specification

BS6580-1992

### Typical Properties

Mobil Coolant Ready Mixed	
Color	Fluorescent Green
Density at 20°C, g/cm <sup>3</sup>	1.08
Boiling Point, °C	>110
Flash Point, °C	> 115
pH value	7.5
Reserve Alkalinity (M/10HCl), ml	10
Water Content, % max	49

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube, SHC are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Asia Pacific Pte Ltd

Jakarta Representative Office

Wisma GKBI 27th Floor

Jl. Jenderal Sudirman No. 28

Jakarta 10210

Indonesia


+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved