



Mobil Super™ Everyday Protection 10W-40

Mobil Passenger Vehicle Lube , South Korea

Synthetic Technology Engine Oil

Product Description

Mobil Super™ Everyday Protection 10W-40 is premium synthetic technology motor oil designed to provide everyday protection for cars under most operating conditions.

Features and Benefits

Mobil Super™ Everyday Protection 10W-40 is meticulously engineered for today's tougher engine specifications. It provides reliable engine protection in everyday driving and helps to extend engine life.

- Designed to provide reliable anti-wear protection
- Protection against LSPI (low speed pre-ignition) events in TGD engines to help prolong engine life
- Helps to maintain engine cleanliness

Applications

Mobil Super™ Everyday Protection 10W-40 is ideally suited for common driving conditions such as highway driving and lower consistent speed conditions in everyday driving.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SP

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	3.6
Density @ 15.6 C, g/ml, ASTM D4052	0.868
Total Base Number, mgKOH/g, ASTM D2896	7.5

Property	
Viscosity Index, ASTM D2270	142
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	20600
Ash, Sulfated, mass%, ASTM D874	0.8
Pour Point, °C, ASTM D97	-33
Flash Point, Cleveland Open Cup, °C, ASTM D92	221
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	91

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved