



Mobil Extra 2T

Mobil Passenger Vehicle Lube , Pacific Islands

Superior Performance Two-Stroke Engine Oil

Product Description

Mobil Extra 2T is a high performance; semi-synthetic, smokeless, two-stroke engine oil developed to meet for high performance motorcycles, snowmobiles and chain saws.

Mobil Extra 2T is pre-diluted to facilitate mixing when added to fuel.

Features and Benefits

Mobil Extra 2T combines a blend of high quality mineral and synthesised high performance baseoils with an advanced additive system to provide excellent engine cleanliness and no-smoke exhaust performance. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Excellent wear protection | Longer engine life |
| Good thermal and oxidation stability and deposit control | Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking, piston tightening and prevention of pre-ignition problems |
| Excellent corrosion protection properties | Longer engine life |
| Smoke-free exhaust | Cleaner environment |

Specifications and Approvals

| Mobil Extra 2T meets or exceeds the requirements of the following industry specifications: | |
|--|-------|
| API | TC |
| ISO | E-GC |
| JASO | FC/FD |

Typical Properties

| Mobil Extra 2T | |
|-----------------------------------|-------|
| Viscosity, ASTM D 445 | |
| cSt @ 40° C | 55 |
| cSt @ 100° C | 8.8 |
| Viscosity Index, ASTM D 2270 | 135 |
| Sulfated Ash, wt%, ASTM D 874 | 0.06 |
| Pour Point, °C, ASTM D 97 | -24 |
| Flash Point, °C, ASTM D 92 | 110 |
| Density @ 15° C kg/l, ASTM D 4052 | 0.867 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Extra 2T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Mobil International Petroleum Corporation
Tour Cogimpa - 19 Avenue Foch,
BP 108, 98845 Noumea Cedex
Nouvelle Calédonie

+687 24 21 50

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved