



## MOBIL SUPER SYNTHETIC TECHNOLOGY 5W-30

Mobil Passenger Vehicle Lube , Pakistan

### Product Description

Mobil Super Synthetic Technology 5W-30 is a synthetic technology motor oils designed to provide a high level of performance and protection under most operating conditions.

### Features and Benefits

Mobil Super Synthetic Technology 5W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Designed to provide very good wear protection
- Helps to maintain engine cleanliness

### Applications

Mobil Super Synthetic Technology 5W-30 is suitable for use in gasoline powered vehicles and ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions.

### Specifications and Approvals

**This product is recommended for use in applications requiring:**

API CF

**This product meets or exceeds the requirements of:**

API SN

ILSAC GF-5

API SM

API SL

### Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	63.6
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.6
Viscosity Index, ASTM D2270	157

Property	
Ash, Sulfated, mass%, ASTM D874	0.9
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.1
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Density @ 15 C, g/ml, ASTM D4052	0.86

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Mobil Askari Lubricants Limited

D-46, Block-5

KDA Scheme-5, Clifton

Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax : (92-21) 583-1013 and 583-0082

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved