



Mobil Super™ 2000 X1 5W-30

Mobil Passenger Vehicle Lube , Poland

Premium Semi-Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 2000 x1 5W-30 is a synthetic technology engine oil that provides everyday protection against sludge and wear to ensure long engine life.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the protection you want from your vehicle. Mobil Super 2000 x1 5W-30, confidence in every journey, provides multiple benefits:

- Reliable wear protection
- High level of sludge prevention
- Engine long life and cleanliness
- Cold start-up protection
- Reliable high temperature protection

Applications

ExxonMobil recommends Mobil Super 2000 x1 5W-30 for:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop-and-go city driving
- Normal to occasionally severe operating conditions
- Standard oil drain up to 15.000km/1 year

Specifications and Approvals

This product has the following approvals:
VW 502 00
AVTOVAZ (LADA cars)

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
ACEA A3/B3
ACEA A3/B4

This product meets or exceeds the requirements of:

API SL

AAE (STO 003) Group B7

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	73.9
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.2
Ash, Sulfated, mass%, ASTM D874	1.2
Phosphorus, mass%, ASTM D4951	0.10
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15.6 C, g/ml, ASTM D4052	0.86
Pour Point, °C, ASTM D97	-33

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland sp. z o.o.

ul.Chmielna 85/87

00-805 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>


Tel +48 22 556 29 00

Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved