



Mobilcut Series

Mobil Industrial , Slovakia

Aqueous Metal Working Fluids

Product Description

Mobilcut is the trademark for Mobil Industrial lubricants line of high performance water miscible metal removal fluids. Formulated with leading edge base oils, additives, and emulsifiers, the Mobilcut series of non-chlorinated products provides dependable performance in a wide array of metal removal processes. The products are designed to work in a variety of hard and soft water qualities and offer low foam potential and long-term corrosion protection for machine and components. Low maintenance and inherently stable, Mobilcut products are designed for the modern machine shop where long service life, excellent machining performance and health and environmental concerns are important factors for increased productivity. These products are supplied in concentrated form and require mixing with water at the point of use.

Mobilcut 100 is a conventional milky soluble oil that readily mixes with different waters to form stable emulsions. Its versatile performance makes it suitable for a wide range of metal cutting and grinding operations for both ferrous and non ferrous materials where economical performance is the main consideration. It offers excellent emulsion stability and long-term corrosion protection for both components and machine tool.

Enhanced with lubricity agents, Mobilcut 140 is a long life water soluble fluid making it an ideal choice for moderate to heavy duty machining applications in the modern machine shop. It is formulated to provide long service life and good emulsion stability and durability while helping to increase tool life and surface finish, even in difficult machining operations. Mobilcut 140 is an ideal choice where excellent machining performance is required for a wide variety of materials and applications while being easy to monitor and maintain.

Mobilcut 210 is a high quality semi synthetic water miscible metalworking fluid designed to form a translucent emulsion over a wide water hardness range. Having a relatively low oil content, the product has good detergent, coolant and cutting properties, making it suitable for a light to moderate duty cutting and grinding applications. Mobilcut 210's formulation makes it particularly recommended for the machining and grinding of cast iron while helping to maintain machine cleanliness.

Mobilcut 250 is a high performance semi-synthetic fluid formulated to enhance performance when machining aluminum and aluminum alloys and where low staining potential is important on sensitive components. Containing high levels of lubricity agents, it provides high machining performance of carbon and alloy steels and yellow metals.

Mobilcut 320 is an inherently stable, synthetic (mineral oil-free) metalworking fluid. It is designed for general grinding operations where a high quality surface finish, outstanding cooling and low foaming potential are the primary requirements. It will help maintain free and open grinding wheels for maximum performance and shows a marked stability for long service life.

Features and Benefits

The Mobilcut series of products are designed to help increase the productivity of modern machine shops by providing high performance features

Features	Advantages and Potential Benefits
Form stable emulsions and solutions	Ease of use and maintenance
Long term inherent stability	Increases batch life and reduces unpleasant odors
Low foaming potential	Improved performance even in high pressure systems
Resists formation of sticky residues	Improves machine cleanliness
High degree of corrosion protection	Reduces machine maintenance and rework of materials

Features	Advantages and Potential Benefits
Good separability from fines	Improves filterability and surface finish
Wide Range of applicability	Potential to consolidate products and reduce inventories
Compatible with high performance Mobil Vactra Oil No slideway lubricants	Easy separation and removal of tramp oil
Neutral Odor	Enhances the workplace environment

Applications

Mobilcut 100: General machining of easy to machine steels and copper alloys in light to moderate duty machining operations such as milling, turning, sawing, boring, drilling and reaming.

Mobilcut 140: Machining of aluminum and high machinability steels in o moderate to heavy duty operations such as milling, turning, sawing, boring, drilling and reaming where the lubricity of a soluble oil is desired.

Mobilcut 210: Machining of ferrous/non ferrous metals in centralized or individual machines. Lower oil content for extra wettability and corrosion protection. Well suited for cast iron machining and grinding.

Mobilcut 250: Semi synthetic cutting fluid primarily intended for the machining of aluminum and aluminum alloys. It may also be used on a wide variety of ferrous materials where a more versatile fluid is required.

Mobilcut 320: Synthetic (mineral oil-free) grinding fluid, primarily recommended for grinding of steels and cast iron.

Properties and Specifications

Property	100	140	210	250	320
Appearance, AA.Lab.101	Brown Liquid		Yellow Liquid		
Appearance, PTM 100		Yellow, Liquid		Brown Liquid	Colourless liquid
Appearance, 3.0% in 15 deg dH Water, AA.Lab.101					Clear
Appearance, 4.0% in 15 deg dH Water, AA.Lab.101			Translucent		
Appearance, 5% in 15 deg dH Water, Visual, AA.Lab.101		Milky			
Appearance, 7.0% in 15 deg dH Water, AA.Lab.101	Milky				
Corrosion Test, 3.0% in 15 deg dH Water, DIN 51360-2					3
Corrosion Test, 4.0% in 15 deg dH Water, DIN 51360-2			4	4	
Corrosion Test, 7.0% in 15 deg dH Water, DIN 51360-2	7				
Emulsion Type @ 3% in 50 ppm water, Rating, PTM 141			Semi-synthetic	Semi-synthetic	Synthetic
Emulsion Type @ 5% in 50 ppm water, Rating, PTM 141		Soluble			
Refractive Index, per deg Brix, %, AA.Lab.105	0.95	1.0	1.85	0.9	1.45
pH at 5% in Distilled Water, PTM 104		9.1			

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved