



## Mobil CVT Fluid FE

Mobil Passenger Vehicle Lube , Thailand

High performance transmission fluid

### Product Description

Mobil™ CVT Fluid FE is high performance, continuously variable transmission fluid designed to meet the service fill use for many Japanese designed vehicles. Mobil CVT Fluid FE provides smoother, consistent all weather step-less shifting, and all-around lubrication protection of the transmission components to help extend transmission service life and provide a smooth driving experience.

### Features and Benefits

Mobil CVT Fluid FE is formulated from select high-quality base oils combined with an advanced additive system to ensure consistent repeatable, smooth, step-less shifts under a broad range of driving conditions, temperatures and transmissions. Key features and benefits include

| Features                                                                                                            | Advantages and Potential Benefits |
|---------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Excellent thermal and oxidation stability for long and consistent transmission performance                          |                                   |
| Optimized friction characteristics provides transmission efficiency and shifting performance                        |                                   |
| Good film-strength and anti-wear properties reduce wear and maintain good transmission life                         |                                   |
| Excellent low-temperature properties provide easier start-ups and improved lubrication at low ambient temperatures  |                                   |
| Effective foam control properties provide consistent shifting performance and reduce fluid losses in severe service |                                   |
| Compatibility with all common seal materials helping the control of oil leakage                                     |                                   |
| Lower viscosity provides fuel consumption benefits compared to higher viscosity CVT Fluids                          |                                   |

### Applications

Mobil CVT Fluid FE is recommended by ExxonMobil for refill of pulley-based continuously variable transmissions in Japanese designed vehicles, except for toroidal CVTs and CVTs that require gear oils <sup>1</sup>.

( <sup>1</sup> Mobil CVT Fluid FE is not suitable for applications where a gear oil or toroidal CVT Fluid is specified. Always consult your owner's manual to check the fluid specifications for your particular vehicle.)

### Properties and Specifications

| Property                                                   |     |
|------------------------------------------------------------|-----|
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 5.2 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 22  |
| Viscosity Index, ASTM D2270                                | 179 |

| Property                                        |       |
|-------------------------------------------------|-------|
| Density @ 15 C, g/cm3, ASTM D4052               | 0.840 |
| Flash Point, °C, ASTM D92                       | 188   |
| Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983 | 8200  |
| Color, Visual                                   | Red   |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2019

Esso (Thailand) Public Company Limited  
3195/17-29 Rama IV Road  
Klong Tan, Klong Toey District  
Bangkok 10110  
Thailand

+66 2 2624 000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved