



**Mobil Pegasus™ 605**  
Mobil Industrial , Vietnam  
Gas Engine Oil

**Product Description**

Mobil Pegasus™ 605 is a high performance natural gas engine oil primarily intended for the lubrication of modern medium and high-speed four-cycle engines operating on fuel that contains corrosive materials such as hydrogen sulphide or halogens (compounds containing chlorine, fluorine, etc.). These engines are generally lean-burn design where increased manifold pressures prevent sufficient lubricant from reaching the valve guide areas resulting in low oil consumption which can lead to valve guide wear and valve recession. This effect also increases the potential for wear and acid attack of upper cylinder components from the corrosive materials generated during combustion. The Mobil Pegasus 605 is a 0.5% ash gas engine oil with exceptional reserve alkalinity designed to offset the negative effects of corrosive materials on engine components. The excellent corrosion protection properties helps prevent corrosive wear in cylinders, valve areas and bearings which can result in longer engine life and lower maintenance costs. Mobil Pegasus 605 provides excellent anti-wear and anti-scuff performance which helps assure minimal piston scoring and low cylinder liner and piston ring wear. This oil can also be used for the lubrication of the reciprocating compressors in landfill and biomass gas applications.

Mobil Pegasus 605 is formulated from high quality mineral base oils combined with an advanced technology, low ash additive system designed to provide excellent protection of engine and compressor components. This product exhibits a high level of chemical stability and resistance to oxidation and nitration. Pegasus 605 offers outstanding resistance to valve train wear and protection against deposit formation. These performance advantages combined with the very effective detergent/dispersancy characteristics helps control the formation of ash and carbon deposits that could result in poor engine performance and detonation. This product is compatible for use in gas engines equipped with catalytic converters.

**Features and Benefits**

Mobil Pegasus 605 Gas Engine Oil provides an additional margin of protection in those applications using contaminated fuel. Its excellent detergent / dispersant technology also results in cleaner engines, lower wear rates and improved engine performance. The use of this product can result in reduced maintenance costs and improved production capacity. Its excellent chemical and oxidation stability can result in longer drain periods and reduced filter costs. The high reserve alkalinity of the product allows its use in engines operating on fuels with low to moderate amounts of corrosive materials in the fuel gas.

| Features  | Advantages and Potential Benefits  |
|---|--|
| Optimised TBN and Reserve Alkalinity            | Controls wear and corrosion when using contaminated gas<br>Protects valve seats and faces on four-cycle engines<br>Controls combustion chamber ash formation and improves spark plug performance |
| Outstanding Anti-wear and Anti-scuff Properties | Lower wear of engine components<br>Reduced scuffing of liners in highly loaded gas engines<br>Provides excellent break-in protection   |
| Excellent Oxidation and Chemical Stability      | Cleaner engines<br>Extended drain intervals<br>Reduced filter costs<br>Excellent resistance to oxidation and nitration   |
| Effective Corrosion Resistance                  | Reduces valve guide wear in four-cycle gas engines<br>Protects bearings and internal components  |
| Exceptional Detergent / Dispersant Properties   | Neutralises formation of acids in the oil<br>Protection of upper cylinder and valve train components<br>Cleaner engines<br>Longer filter life  |
| Non-zinc and Non-phosphorus Formulation         | Improves catalytic converter performance and longer life   |

Applications

Note: Engines operating on fuel gas with elevated levels of sulphur or halogens should also have coolant (jacket water) and oil temperatures raised.

- Gas engines operating on fuel that contains moderate levels of hydrogen sulphide (H2S)
- Engines operating on fuel containing other corrosive materials such as TOHCl (Total Organic Halides as Chloride) such as landfill or biomass gas
- Spark ignited four-cycle gas engines with very low lube oil consumption
- Medium and high speed four-cycle engines equipped with catalytic converters requiring a low ash gas engine oil
- Engines experiencing valve train wear and corrosion
- Reciprocating compressors operating on natural gas that contains sulphur or chlorine compounds
- High output or naturally aspirated engines operating at or in excess of rated capacity under high temperatures

Specifications and Approvals

|   |
|---|
| <b>This product has the following approvals:</b>  |
| INNIO Waukesha Engine Landfill Gas Applications   |
| Caterpillar Energy Solutions TR 2105, Lube Oils for Gas Engines (CG132, CG170, CG260)   |
| Rolls-Royce Solutions Augsburg (former MTU Onsite Energy) Gas Engines Series 400 - all engines with natural gas and propane gas |
| MWM TR 0199-99-2105, Lube Oils for Gas Engines  |

|   |
|---|
| <b>This product meets or exceeds the requirements of:</b> |
| Caterpillar   |

Properties and Specifications

| Property   |        |
|--|--------|
| Grade  | SAE 40 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445              | 13.2   |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445               | 124    |
| Viscosity Index, ASTM D2270                                | 100    |
| Ash, Sulfated, mass%, ASTM D874                            | 0.5    |
| Base Number - Xylene/Acetic Acid, mg KOH/g, ASTM D2896 (*) | 7.0    |
| Pour Point, °C, ASTM D97                                   | -15    |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 262    |
| Density 15.6 C, lb/gal, CALCULATED                         | 0.890  |

(\*) use of other ASTM approved solvents may yield different results

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved