



Mobiltrans MBT 75W-90

Mobil Commercial Vehicle Lube, Hong Kong

性能卓越的變速箱潤滑油

產品說明

Mobiltrans MBT 是一種 SAE 75W-90 全合成手動變速箱油。Mobiltrans MBT 75W-90 具有優異的黏度/溫度特性。

特性和效益

Mobiltrans MBT 的配方採用先進的添加劑系統，因此能夠提供出色的熱穩定性和耐磨損性。與傳統的變速器油相比，Mobiltrans MBT 能在變速箱中維持更低的溫度。我們建議將此產品用於大多數手動變速箱、傳動軸和無需使用 API GL-5 潤滑油的輕微準雙曲面車軸。Mobiltrans MBT 適用於車輛滿載運作時潤滑油需要處於極高溫度環境的變速箱(齒輪箱)。

應用方式

Mobiltrans MBT 已獲平治規格表 MB 235.11 認可，該規格表涵蓋 Actros 手動變速器，包括附帶分動箱的變速器。

規格與認證

此產品取得以下認可：
MB-Approval 235.11

屬性與規格

屬性	
等級	SAE 75W-90
-40°C 條件下的布氏黏度, mPa*s, DIN 51398	59000
閃火點(克利夫蘭敞口杯), °C, DIN 2592	179
100°C 條件下的運動黏度, mm ² /s, DIN 51562 T1	14.7
40°C 條件下的運動黏度, mm ² /s, DIN 51562 T1	96.3
流動點, °C, DIN ISO 3016	-45
黏度指數, DIN 2909	159

健康與安全

有關本產品的健康和 safety 建議，請參見物質安全資料表 (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有說明，否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標

12-2019

ExxonMobil Hong Kong
22nd Floor, Central Plaza,

18 Harbour Road, Wanchai

Hong Kong

+852 3197 8888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved