



**Primol 382**  
ExxonMobil Specialties , Denmark  
Medicinal grade White Oil

**Product Description**

Primol 382 is a purified mixture of liquid saturated hydrocarbons. It is a colourless, transparent oily liquid and is essentially odourless and tasteless. It is obtained from petroleum through several refining stages, including an ultimate purification by catalytic hydrogenation.

Primol 382 is manufactured to exceed the purity requirements of the Pharmacopoeias Due to its superior chemical inertness, it demonstrates better colour and oxidative stability than most mineral and vegetable oils, when stored and used under controlled conditions.

ExxonMobil White Oils are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

CAS number: 8042-47-5

EINECS number: 232-455-8

INCI name (Europe): Paraffinum Liquidum

CTFA Dictionary name (USA): Mineral Oil

**Applications**

Primol 382 can be used in a variety of food-related, cosmetic and pharmaceutical applications subject to the applicable laws and regulations in each country (\*).

Thermoplastics

- Primol 382 is recommended as a food packaging-grade plasticizer in Polystyrene. It combines outstandingly low volatility and excellent compatibility with Polystyrene for optimal performance in General Purpose and High Impact PS grades.
- Primol 382 is recommended for use as an external lubricant for non-plasticized PVC.
- Primol 382 is an inert and protective catalyst carrier for polypropylene processes. It can also serve as a pigment powder dispersant in master batch compounding.

Elastomers and Adhesives

- Primol 382 is used for producing food-contact or medical rubber articles such as EPDM or butyl rubber. It is particularly well suited for the extension of Thermoplastic Elastomers (TPE), such as SBS, SEBS or SEPS.
- Primol 382 is also recommended for Hot-Melt Adhesives formulations used in sanitary products.

Cosmetics and Pharmaceuticals

- Primol 382 has many well-established applications in the pharmaceutical industry, like laxative jellies and ointments, and is also recommended as a component for many cosmetic products, such as creams and body lotions.

(\*) User must check compliance with applicable regulations.

**Regulations and Claims**

|                                                           |
|-----------------------------------------------------------|
| <b>This product is registered to the requirements of:</b> |
| NSF H1                                                    |

**This product meets or exceeds the requirements of:**

FDA 21 CFR 178.3620(a)

European Pharmacopoeia, Liquid Paraffin monograph

US Pharmacopeia/National Formulary Mineral Oil monograph

European Regulation (EU) 10/2011

**Properties and Specifications**

| Property                                        | Standard Method(a) | Typical | Min                         | Max   |
|-------------------------------------------------|--------------------|---------|-----------------------------|-------|
| Appearance                                      | Visual             |         | Clear and Bright            |       |
| Density @ 15 C, kg/m <sup>3</sup>               | ASTM D4052         |         | 863                         | 873   |
| Distillation, 10 torr, 2.5%, °C                 | ASTM D1160         | 288     |                             |       |
| Distillation, 10 torr, 5.0%, °C                 | ASTM D1160         | 291     | 288                         |       |
| Distillation, 10 torr, 10%, °C                  | ASTM D1160         | 295     | 292                         |       |
| Flash Point, Cleveland Open Cup, °C             | ASTM D92           |         | 240                         |       |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s | ASTM D445          |         | 8.6                         |       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s  | ASTM D445          |         | 67.0                        | 78.0  |
| Odor                                            | OLFACTORY          |         | odorless or almost odorless |       |
| Pour Point, °C                                  | ASTM D5950         |         |                             | -9    |
| Refractive Index, 20 C                          | ASTM D1218         |         | 1.473                       | 1.478 |
| Relative Density @ 20 C/20 C                    | ASTM D4052         |         | 0.861                       | 0.872 |
| Relative Density @ 25 C/25 C                    | ASTM D4052         |         | 0.859                       | 0.870 |
| Color, Saybolt                                  | ASTM D6045         |         | +30                         |       |
| Average Molecular Weight, g/mole                | ASTM D2502         |         | 485                         |       |
| Hydroc. with less than 25 carbons, wt %         | ASTM D6352         |         |                             | 3     |
| Paraffinic Carbons (C <sub>p</sub> ), %         | AM-S 1805          | 68      |                             |       |
| Naphthenic Carbons (C <sub>n</sub> ), %         | AM-S 1805          | 32      |                             |       |
| Aromatic Carbons (C <sub>a</sub> ), %           | AM-S 1805          | 0       |                             |       |
| Dynamic Viscosity @ 20 C, mPa.s                 | CALCULATED         |         | 175                         | 230   |

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

ExxonMobil Lubricants & Specialties Europe

Hermeslaan 2

1831 Machelen

BELGIUM

+32-2-722-2111

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

**ExxonMobil**

Exxon

Mobil

Esso

XTO  
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All  
Rights Reserved