



Prowaxx™ 1088 HS

ExxonMobil Specialties , Mexico

Product Description

Prowaxx 1088 HS is an ultra-low melt point, hydrofined soft wax product. It is designed to be used as a component in a final wax blend or emulsion. Prowaxx 1088 HS is a translucent, soft, waxy material in the solid state and is a low viscosity, clear liquid when molten. It is produced as the co-product of deoiling fully-refined wax and is then catalytically hydrofined for exceptional water white color. It is a mixture primarily composed of branched, iso-paraffin hydrocarbons and normal paraffins.

Prowaxx 1088 HS meets the requirements for the Food and Drug Administration (FDA) standards for indirect food contact substances and contains an oxidation inhibitor to improve stability.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Prowaxx 1088 HS is used in a wide variety of applications and is subject to applicable laws and regulations in each jurisdiction\*. Suitability in each application is the responsibility of the user.

- Candle wax blends
- Wax emulsions and blends
- Fire starters and logs
- Raw material for lubricants and greases
- Dust control for roofing granules, roads, fertilizer, and others

\*User must check compliance with applicable regulations.

Regulations and Claims

|                               |
|-------------------------------|
| <b>PROWAXX 1088 HS meets:</b> |
| FDA 21 CFR 178.3710           |

Properties and Specifications

| Property                            | Standard Method(a) | Min | Max |
|-------------------------------------|--------------------|-----|-----|
| Saybolt Color                       | ASTM D156          | +28 |     |
| Flash Point, Cleveland Open Cup, °C | ASTM D92           | 204 |     |
| Congealing Point, °C                | ASTM D938          | 36  | 48  |
| Odor, Wax                           | ASTM D1833         |     | 1   |

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method

specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2023

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

<http://www.exxonmobil.com>

(01 52) 55 5-333-9602 (01 52) 1-800 90-739-00

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved