



Mobil Delvac Legend™ 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Azerbaijan

High Performance Diesel Engine Oil.

Product Description

Mobil Delvac Legend 15W-40 Heavy Duty is a Multigrade synthetic Blend diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac Legend 15W-40 Heavy Duty is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying and agricultural industries

Features and Benefits

| Features                          | Advantages and Potential Benefits                              |
|-----------------------------------|----------------------------------------------------------------|
| Thermal and oxidation stability   | Helps to control sludge build-up and deposits                  |
| TBN reserve                       | Helps to control deposits                                      |
| Stay-in-grade shear stability     | Helps to reduce oil consumption and to provide wear protection |
| Excellent detergency/ dispersancy | Helps to protect and to maintain engines clean                 |
| Component compatibility           | Long gasket and seal life                                      |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying and agriculture

Specifications and Approvals

| This product has the following approvals: |
|-------------------------------------------|
| MTU Oil Category 2                        |
| DTFR 15B110                               |

| This product is recommended for use in applications requiring: |
|----------------------------------------------------------------|
| ACEA E3                                                        |
| API CF                                                         |

**This product is recommended for use in applications requiring:**

API CF-4

API CG-4

Mack EO-M

VOLVO VDS-2

ACEA B2

MAN M 3275-1

RENAULT TRUCKS RD

RENAULT TRUCKS RD-2

RENAULT TRUCKS RLD

API SH

**This product meets or exceeds the requirements of:**

API CH-4

API SJ

**Properties and Specifications**

| Property                                                   |            |
|------------------------------------------------------------|------------|
| Grade                                                      | SAE 15W-40 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 116        |
| Pour Point, °C, ASTM D97                                   | -33        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 15.2       |
| Ash, Sulfated, mass%, ASTM D874                            | 1.1        |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 233        |
| Viscosity Index, ASTM D2270                                | 137        |
| Total Base Number, mgKOH/g, ASTM D2896                     | 8          |
| Density @ 15 C, kg/l, ASTM D4052                           | 0.869      |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

