



Mobil Delvac™ Super 1300 C

Mobil Commercial Vehicle Lube , 中国

Synthetic Technology

Product Description

Mobil Delvac™ Super 1300 C products are high performance diesel engine oils that provide proven engine protection of diesel engines operating in on and off-highway severe service applications. Mobil Delvac Super 1300 C products are recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Super 1300 C products delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product meets or exceeds the requirements of the following industry specification:	10W-30	15W-40
API CH-4		X

This product meets or exceeds the requirements of:	10W-30	15W-40
API CH-4	X	

Properties and Specifications

Property	10W-30	15W-40	20W-50
----------	--------	--------	--------

Property	10W-30	15W-40	20W-50
Grade	SAE 10W-30	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1.1	1.1	1.1
Density @ 15 C, kg/l, ASTM D4052		0.869	0.872
Flash Point, Cleveland Open Cup, °C, ASTM D92	225	233	245
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.7	15.2	20.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	79.5	116	174
Pour Point, °C, ASTM D97	-36	-33	-30
Total Base Number, mgKOH/g, ASTM D2896	9	8	9
Viscosity Index, ASTM D2270	141	137	135

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved