



Mobil Super™ Full Synthetic 0W-20

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

Mobil Super Full Synthetic 0W-20 is a full synthetic engine oil, designed to provide instant protection of your engine under various road conditions, enable you to explore every corner of the city with no worries and enjoy the whole journey.

Features and Benefits

- Meet with API SP grade, help to protect LSPI problem of turbo engine
- Allows easy and smooth starting during cold starts, protecting critical engine parts with good fluidity in low temperature.
- Provide engine strong wear protection in high temperature and keeps engine clean
- Help to enhance Fuel Efficiency.

Applications

Mobil Super Full Synthetic 0W-20 is recommended for gasoline vehicles with 0W-20 viscosity grade recommended.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6A
FORD WSS-M2C962-A1

Properties and Specifications

Property	
Grade	SAE 0W-20
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	14000
Viscosity Index, ASTM D2270	161
Total Base Number, mgKOH/g, ASTM D2896	8.8
Density @ 15 C, g/ml, ASTM D1298	0.845
Flash Point, Cleveland Open Cup, °C, ASTM D92	237
Pour Point, °C, ASTM D97	-48

Property	
Ash, Sulfated, mass%, ASTM D874	0.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	46
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.4
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved