



Mobil Super™ 1000 20W-50

Mobil Passenger Vehicle Lube , Colombia

Product Description

Mobil Super™ 1000 20W-50 is brought to you by the makers of Mobil 1. This premium mineral engine oil is designed for extended engine life and meet your most demanding vehicle maintenance needs.

Features and Benefits

- Suitable for most Japanese and Korean gasoline engines
- Improve engine efficiencies by reducing Engine Low Speed Pre-Ignition (LSPI)
- Extended protection against deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super™ 1000 20W-50 have been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super 1000 Everyday Protection for daily driving under normal conditions:

- Nearly all gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SM

API SN

API SN PLUS

This product meets or exceeds the requirements of:

API SP

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 20W-50 |
| Pour Point, °C, ASTM D97 | -27 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 167 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 19.5 |
| Flash Point, °C, ASTM D92 | 252 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.87 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

Organización Terpel S.A.


Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved