



## Mobil Super™ Everyday Protection 5W-40

Mobil Passenger Vehicle Lube , Croatia

High Quality Engine Oil

### Product Description

Mobil Super™ Everyday Protection 5W-40 is a high quality engine oil that provides long life for gasoline & diesel engines for vehicles of all ages.

### Features and Benefits

Mobil Super™ Everyday Protection 5W-40 helps provide:

- High temperature protection
- Cold start-up protection
- Engine cleanliness and sludge prevention
- Wear protection

### Applications

Mobil Super™ Everyday Protection 5W-40 is suitable for:

- Passenger cars, SUV's, light trucks and vans
- Gasoline and Diesel engines, without particulate filters
- Stop and go city driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**According to ExxonMobil, MOBIL SUPER EVERYDAY PROTECTION 5W-40 is of the following quality level:**

ACEA A3/B3-16

API CF-4

API CF

According to ExxonMobil, MOBIL SUPER EVERYDAY PROTECTION 5W-40 is of the following quality level:

API CG-4

This product meets or exceeds the requirements of:

ACEA A3/B4

API SL

API SM

API SN

### Properties and Specifications

Property	
Grade	SAE 5W-40
Viscosity Index, ASTM D2270	165
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	85
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Density @ 15 C, g/ml, ASTM D1298	0.861

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved