



Mobil Super™ 3000 X4 5W-40

Mobil Passenger Vehicle Lube , Peru

Premium Full Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 3000 X4 5W-40 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

Features and Benefits

Mobil Super™ 3000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super™ 3000 X4 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

Applications

Mobil Super™ 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend Mobil Super™ 3000 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:	
MB-Approval 229.3	
MB-Approval 229.5	
VW 502 00	
VW 505 00	
Porsche A40	
PSA B71 2296	
BMW Longlife 01	
RENAULT RN0700	
RENAULT RN0710	
AVTOVAZ (LADA cars)	

This product is recommended for use in applications requiring:	
API CF	
FIAT 9.55535-G2	

This product meets or exceeds the requirements of:	
AAE (STO 003) Group B7	
API SL	
API SM	
API SN	
API SN PLUS	
API SP	
Fiat 9.55535-M2	
ACEA A3/B3	
ACEA A3/B4	

Properties and Specifications

Property	
Grade	SAE 5W-40

Property	
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	78
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.1
Density @ 15.6 C, g/ml, ASTM D4052	0.85
Viscosity Index, ASTM D2270	169

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2023

Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved