



Mobil Super 3000 Formula P 5W30

Mobil Passenger Vehicle Lube , Slovenia

High Performance Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super 3000 Formula P 5W-30 is a high performance, low ash engine oil designed to help prolong engine life and maintain the efficiency of the exhaust emission reductions systems in both diesel and gasoline powered passenger cars, light commercial vehicles and vans.

This product is recommended for use in Peugeot, Citroën vehicles and a wide range of European cars and light-duty commercial vehicles which need to meet or exceed requirements of ACEA C2.

Features and Benefits

Mobil Super™ 3000 Formula P 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

- Low Ash, low phosphorous and low sulfur formulation helping to prolong the life and maintain the efficiency of the emission reduction systems in both Diesel and gasoline powered engines.
- Compatible with Diesel Particulate Filters and Catalytic Convertors.
- Help achieve fuel economy (as per ACEA C2).
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine and electrical system protection.
- High performance wear-protection (as per ACEA).
- Active cleaning agents help prevent deposits and sludge build-up and enable long and clean engine life.

Applications

Mobil Super™ 3000 Formula P 5W-30 is recommended for a variety of modern automotive engines, especially the high-performance gasoline, turbo-diesel injection with common rail and other diesel engines, found in the latest passenger cars, SUV's and light vans.

- Peugeot-Citroën passenger cars and light commercial vehicles or vans
- Passenger cars and light commercial vehicles or vans requiring ACEA C2 like Iveco and Fiat vans
- Gasoline and Diesel with Diesel Particulate Filters (DPF) and Catalytic Convertors
- Normal to occasionally severe operating conditions (including city driving conditions)

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle. Not recommended for 2-cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

This product has the following approvals:
PSA B71 2290
This product meets or exceeds the requirements of:
ACEA C2
FIAT FIAT 9.55535-S1

Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15 C, g/ml, ASTM D1298	0.853
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	57
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	9.9
Viscosity Index, ASTM D2270	160
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	234

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved