



MOBIL SUPER SYNTHETIC EURO X1 5W30

Mobil Passenger Vehicle Lube , Thailand
Premium Full Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ Synthetic Euro X1 5W-30 is a premium full synthetic engine oil, designed to provide outstanding levels of protection for modern vehicles in city driving.

Features and Benefits

eMobil Super Synthetic Euro X1 5W-30 is industry proven so you can enjoy the freedom and convenience of driving with engine well protected from harsh conditions of city driving.

Mobil Super Synthetic Euro X1 5W-30 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

Mobil Super Synthetic Euro X1 5W-30 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend this product if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

Specifications and Approvals

This product has the following approvals:
BMWLonglife-01
MB229.3
VW502 00
VW505 00

This product is recommended for use in applications requiring:
--

This product is recommended for use in applications requiring:

APICF

This product meets or exceeds the requirements of:

APISJ

APISL

ACEAA3/B3-16

ACEAA3/B4-16

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	66
Viscosity Index, ASTM D2270	181
Density @ 15 C, g/cm ³ , ASTM D4052	0.848
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	245
Ash, Sulfated, mass%, ASTM D874	1.2
Total Base Number, mgKOH/g, ASTM D2896	10.1
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	21700
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Marketing (Thailand) Limited

3195/26, 22nd Floor, Rama IV Road

Klong Ton, Klong Toey District

Bangkok 10110

Thailand

+66 2 407 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All
Rights Reserved