



PAVING ASPHALT C320 TPI

ExxonMobil Asphalt , Australia
Viscosity Graded Asphalt Product

Product Description

Paving Asphalt C320 TPI is a viscosity graded asphalt product.
The specifications apply to those asphalt acquired for resale by ExxonMobil through purchase or exchange from third party supplier.

Applications

Paving Asphalt C320 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use

Properties and Specifications

Property	Limit	Standard Method	
Dynamic Viscosity @ 60 C, Pa.s	Min-Max	ASTM D2171	260-380
Penetration, 25C, 100g, 5s, dmm	Min	ASTM D5	40
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	250
Matter Insoluble in Trichloroethylene, wt%	Max	ASTM D2042	1.0
Density @ 15 C, kg/m3	Min	ASTM D70	REPORT
Viscosity @ 60°C, on ASTM D6 residue, as percentage of original, %	Max	ASTM D2171	300

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.
05-2020

ExxonMobil

Exxon

Mobil

ESSO

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved

