



Paving Asphalt C170 TPI

ExxonMobil Asphalt , Australia

Viscosity Graded Asphalt Product

Product Description

Paving Asphalt C170 TPI is a viscosity graded asphalt product.
The specifications apply to those asphalt acquired for resale by ExxonMobil through purchase or exchange from third Party supplier.

Applications

Paving Asphalt C170 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties and Specifications

Property	Limit	Standard Method(a)	
Dynamic Viscosity @ 60 C, Pa.s	Min-Max	ASTM D2171	140-200
Viscosity @ 135°C, Pa.s	Min-Max	ASTM D4402	0.25-0.45
Penetration, 25C, 100g, 5s, dmm	Min	ASTM D5	62
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	250
Matter Insoluble in Trichloroethylene, wt%	Max	ASTM D2042	1.0
Density @ 15 C, kg/m3	Min	ASTM D70	REPORT
Viscosity @ 60°C, on ASTM D6 residue, as percentage of original, %	Max	ASTM D2171	300

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.
05-2020

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved

