



EHC™ 20L

ExxonMobil Basestocks , Australia

Product Description

EHC™ base stocks by ExxonMobil are designed for performance capability in a broad range of finished lubricant applications. EHC™ 20L is an extra light neutral base stock suitable for a variety of low viscosity lubricants, such as those utilized in automotive driveline, hydraulic, and thermal management applications. The use of EHC™ 20L allows for the reduction of Group III components, while still meeting performance targets. ExxonMobil follows rigorous processes to ensure reliable delivery of consistent quality base stocks so customers can be confident in their base stock supply.

Features and Benefits

EHC 20L delivers quality that enables our customers to produce high performance lubricants. Key features include:

- Excellent low temperature properties and pour point
- Low aromatics for exceptional oxidation and thermal stability
- Product specifications that enable formulators to meet or exceed industry/OEM requirements
- Light color

Specifications

Property	Limit	Standard Method(a)	
Saybolt Color	Min	ASTM D156	10
Viscosity Index	Min	ASTM D2270	85
Kinematic Viscosity @ 100 C, mm ² /s	Min-Max	ASTM D445	2.1-2.6
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	150
Pour Point, °C	Max	ASTM D97	-30
Appearance	Min-Max	Visual	Clear and Bright
Kinematic Viscosity @ 40 C, mm ² /s	Min	ASTM D445	7

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
ExxonMobil
3225 Gallows Road
Fairfax, VA 22037-001

1-800-662-4592
<http://www.exxonmobil.com>

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

The ExxonMobil logo is displayed in white text on a dark background. The word "Exxon" is in a bold, sans-serif font, and "Mobil" is in a slightly lighter, sans-serif font.

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved