



Canthus 1000

ExxonMobil Basestocks , Belgium

Product Description

ExxonMobil produces specialized base stocks that offer a wide span of properties and are broadly used in the lubricant industry. Canthus 1000 is a very high viscosity straight mineral oil for economical lubrication of heavy industrial machinery and as ingredient for blenders of lubricants for many industrial applications, including marine. With this selected product and the other base stock slates, ExxonMobil is the recognized market leader for Group I base stocks.

Canthus 1000 is available by truck, rail, barge and vessel.

Features and Benefits

Consistent base stock formulations help simplify operations. Canthus 1000 and other specialized base stocks by ExxonMobil are produced following rigorous processes to ensure reliable delivery of consistent quality so customers can be confident in their base stock supply. Benefits include:

- Unique stocks tailored to applications
- Consistence performance in formulations
- Superior supply chain/delivery logistics

Specifications

Property	Limit	Standard Method(a)	
Appearance	Min-Max	Visual	Clear and Bright
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	298
Kinematic Viscosity @ 40 C, mm ² /s	Min-Max	ASTM D445	900-1,000
Pour Point, °C	Max	ASTM D97	-3
Viscosity Index	Min	ASTM D2270	80

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

ExxonMobil Petroleum & Chemical BV

Polderdijkweg, 2030 Antwerp, Belgium

Tel. +32-2-239.3111

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved