



## ExxonMobil Premium HDME 50

ExxonMobil Commercial Fuel , Canada

### PRODUCT DESCRIPTION

ExxonMobil Premium HDME 50 is an Emission Controlled Area (ECA) compliant fuel which combines some of the unique features of a heavy fuel oil (HFO) with those of a marine gas oil (MGO).

It has better ignition qualities compared with HFO and also possesses inherent lubricity characteristics. These characteristics ensure peak combustion and minimize wear on internal moving parts within the fuel system that rely on the fuel for lubrication. ExxonMobil Premium HDME 50 has a viscosity higher than MGO resulting in easier handling of fuel switch-over operations and also optimizing proper injection viscosity and fuel atomization with an increased engine operational efficiency. This also means that chillers are not required to be installed.

### FEATURES AND BENEFITS

- Higher viscosity compared to MGO, meaning easier handling compared with MGO. No requirement for chillers/coolers to be installed
- No residual material. Cleaner engines without cat-fines and low ash build up in engine
- Higher flashpoint compared with MGO providing safer handling in boilers
- Excellent ignition quality
- Better volumetric energy content of the new fuel compared with MGO
- Excellent lubricity
- Meets and exceeds ISO 8217:2017 RMD 80

### APPLICATION

- For vessels running in a 0.10% sulphur ECA compliant environment.
- A pour point closer to HFO means that the product is to be stored in heated tanks and treated in heated fuel systems.
- When sulfur levels over 1.00% are present, comingling 10% -15% or greater with low sulfur HFO may result in asphaltene precipitation due to the reduced solvency action of the product. Since it is impossible to identify all crude sources from previous fuels bunkered operators should take a cautious approach and limit comingling of ExxonMobil Premium HDME 50 and existing low sulfur HFO to 2% or less.
- Cetane Index is not an applicable measure of ExxonMobil Premium HDME 50 ignition qualities and CCAI is used instead. Likewise the product is not clear and bright but green / brown in color. This coloration is due to the refining and processing of the fuel and is not an indication of residual product in the fuel.

### TYPICAL PROPERTIES

Kinematic Viscosity	
cSt @ 50°C	30 - 45
Density @ 15°C kg/m <sup>3</sup>	900 - 915
Cetane Index	N/A
CCAI	795 - 810
Sulfur Content, mass %	<0.10
Flash Point, °C	> 70
Hydrogen Sulfide, mg/kg	< 1
Acid Number, mg KOH/g	< 0.1
Total Sediment - existent, mass %	< 0.01
Total Sediment - aged, mass %	0.01

Kinematic Viscosity	
Oxidation Stability, mass %	< 0.01
Carbon Residue, mass %	< 0.30
Pour Point, °C	6-12
Appearance	Brown / green , opaque
Water, vol %	0.05
Ash, mass %	< 0.01
HFRR lubricity, microns	<320
Vanadium, mg/kg	< 1
Sodium, mg/kg	< 1
Al + Si, mg/kg	<5
Ca, mg/kg	< 1
Zn, mg/kg	< 1

## HEALTH AND SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Safety Data Sheet (SDS). SDSs are available upon request through your sales contract office, or via the Internet on <http://www.exxonmobil.com>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Exxon logotype, the Running Tiger are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly. Additional health and safety information on this product can be found on the Material Safety Data Sheet, which is available on line at [www.imperialoil.ca](http://www.imperialoil.ca), or by contacting Lubricants and Petroleum Specialties, Technical Help Desk, 1-800-268-3183. © 2001 Imperial Oil.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved