



Waxrex 715

ExxonMobil Specialties , Chile

Product Description

Waxrex 715 is a high quality saturating wax for corrugated paperboard. It is a translucent crystalline material in the solid state and an essentially water white, clear when molten. Waxrex 715 comprises a blend of refined paraffin waxes and a carefully selected additive system. Application of this product to corrugated paperboard imparts excellent water resistance, high compressive strength in both wet and dry service, scuff resistance and good score line flexibility. A high blocking point minimizes the tendency for blockage during shipping and storage of finished saturated cartons. Waxrex 715 meets applicable Food and Drug Administration (FDA) requirements for food-related uses.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Waxrex 715 is primarily used in the following applications subject to applicable laws and regulations in each jurisdiction\*:

- Wax coating for corrugated paper cartons
- Wax coating for paper packaging

\* User must check compliance with applicable regulations

Properties and Specifications

Waxrex 715 meets applicable Food and Drug Administration (FDA) requirements for food, health and cosmetic- related uses as noted below:

- 21 CFR 176.170 Components of paper and paperboard in contact with aqueous and fatty foods;
- 21 CFR 176.180 Components of paper and paperboard in contact with dry food; and
- 21 CFR 175.105 Adhesives as components of articles intended for use in packaging, transporting or holding of food.

Batch Release Tests	Units	Methods	Min	max
ATSM Saybolt D156 Color	none	ASTM D6045	15	-
Congeeing Point	°C (F)	ASTM D87	52.8(127)	57.2(134.9)
Odor,Wax	none	ASTM D1833	-	1
Flash Point, COC	°C (F)	ASTM D92	204(400)	-

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

- Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.
- Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit in expressing the limiting value in accordance to the ASTM E 29 method

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
COPEC S.A.  
Isidora Goyenechea 2915, Las Condes, Santiago Chile

Número de Teléfono de Información Toxicológica 24 Horas (56) 2-27771994  
Número de Teléfono del Proveedor (56) 2-26907000  
Número de teléfono de emergencia 24 horas (56) 2-26753713

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied

the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

