



## Mobilgard ADL Series

ExxonMobil Marine , Ethiopia

Diesel Engine Oils

### Product Description

Mobilgard™ ADL Series oils have been designed for high Brake Mean Effective Pressure (BMEP) medium- and high-speed diesel engines operating on distillate fuels.

Mobilgard™ ADL 30 and Mobilgard™ ADL 40 oils each have a balanced formulation which combats lacquer formation and deposits in severe service applications. Superior load carrying properties help to minimise piston ring and liner wear, and also make the lubricants suitable for marine gearing applications.

Potential benefits of using Mobilgard ADL Series lubricants include helping:

- Extend component and critical wear surface life
- Improve overall engine cleanliness
- Reduce oil consumption
- Increase time between engine overhauls

### Features and Benefits

Mobilgard ADL Series oils have demonstrated superior performance in the latest model diesel engines, including engines of MAN Energy Solutions Augsburg, Caterpillar (3600 and C280 Series), Deutz, and Wärtsilä. In extensive field testing on these engines, Mobilgard ADL Series oils corrected many problems normally associated with severe service engines operating on lower quality fuels. Results included dramatically reduced oil consumption, significantly reduced liner lacquering and extended periods between overhauls. These advanced diesel lubricants possess excellent water separation, rust and corrosion resistance properties.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Increased thermal and oxidation stability	Improved engine cleanliness, reduced liner lacquering, reduced top deck sludge, reduced piston ring groove deposits and bore polishing
Superior wear protection	Extends the life of critical wear surfaces
Enhanced detergency/dispersancy capability	Reduced deposits especially in the ring belt area which leads to extended cylinder overhauls and reduced oil consumption
Stay-in-grade shear stability	Reduced oil consumption and improved bearing protection
High TBN levels	Prevents corrosive wear due to higher sulphur fuels
Broad range of engine applications	One severe service engine lubricant for all shipboard applications

### Applications

Mobilgard ADL Series lubricants are intended for use in high BMEP engines and in severe duty engine applications where the nature of the fuel and

service requires a greater level of detergency/dispersancy and liner lacquer control than is offered by most diesel engine lubricants.

### Specifications and Approvals

<b>This product has the following approvals:</b>	<b>ADL 30</b>	<b>ADL 40</b>
Anglo Belgian Corporation 12V-DZ, 16V-DZ (Dual Fuel – gas mode)		X
Anglo Belgian Corporation 6DZ, 8DZ (Dual Fuel – gas mode)	X	
GE Transportation GE16V250 Fundamental Approval (letter on file)		X
Caterpillar/MaK 4-Stroke Medium Speed Diesel Engine (Distillate)		X
MAN Energy Solutions Augsburg (Heritage MAN B&W) 28/33D engines		X
MAN Energy Solutions Augsburg (Heritage MAN B&W) 4 Stroke medium speed engines for Alternating Distillate / LNG operation	X	X
MTU Oil Category 2	X	X
Ortlingshaus-Werke Gmbh ON 9.2.10	X	
Wartsila Medium Speed Diesel Engine	X	X
ZF TE-ML 04B	X	X

<b>This product is recommended for use in applications requiring:</b>	<b>ADL 30</b>	<b>ADL 40</b>
ACEA E2	X	X
API CF	X	X
API SF	X	X
MAN 270	X	X

<b>This product meets or exceeds the requirements of:</b>	<b>ADL 30</b>	<b>ADL 40</b>
Anglo Belgian Corporation 12V-DZ, 16V-DZ (with distillate fuel up to 1,5% Sulfur)		X
Anglo Belgian Corporation 6DZ, 8DZ (with distillate fuel up to 1,5% Sulfur)	X	

### Properties and Specifications

<b>Property</b>	<b>ADL 30</b>	<b>ADL 40</b>
Grade	SAE 30	SAE 40
Ash, Sulfated, mass%, ASTM D874	1.4	1.4
Flash Point, Cleveland Open Cup, °C, ASTM D92	230	239
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	11.5	14.7

Property	ADL 30	ADL 40
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	90	132
Pour Point, °C, ASTM D97	-30	-21
Total Base Number, mgKOH/g, ASTM D2896	12	12
Viscosity Index, ASTM D2270	117	112

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022

ExxonMobil Marine Limited  
Ermyn Way  
Leatherhead, Surrey  
United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Energy lives here™

**ExxonMobil**

Exxon Mobil ESSO XTO

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved