



Mobilgard DEO Series

ExxonMobil Marine , Sri Lanka

High Speed Diesel Engine Oil

Product Description

Mobilgard™ DEO (Diesel Engine Oil) Series are high performance monograde diesel engine oils formulated with high quality base stocks and a balanced additive package for use in marine applications.

Features and Benefits

| Features | Advantages and Potential Benefits |
|--|---|
| Extended TBN reserve | Protects engine parts from corrosive wear and deposits Controls formation of acids when using higher sulfur fuels |
| Good protection against oil thickening and sludge built-up | Prolonged engine life |
| Excellent thermal and oxidation stability | Keeps engines clean and operating smoothly |
| Increased high temp/high shear performance | Reduced engine scuffing, bore polishing and ring sticking |

Applications

Mobilgard DEO Series are designed to provide superior performance in severe marine applications, especially for older and reconditioned marine high speed engines. Mobilgard™ DEO Series are used in engines where a monograde lubricant is recommended requiring API CF or CD.

Specifications and Approvals

| This product is recommended for use in applications requiring: | MOBILGARD DEO 30 | MOBILGARD DEO 40 |
|--|------------------|------------------|
| API CD | X | X |
| API CF | X | X |

Properties and Specifications

| Property | MOBILGARD DEO 30 | MOBILGARD DEO 40 |
|---|------------------|------------------|
| Grade | SAE 30 | SAE 40 |
| Ash, Sulfated, mass%, ASTM D874 | 1.1 | 1.1 |
| Density @ 15 C, g/cm3, ASTM D4052 | 0.89 | 0.9 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 256 | 254 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 11.8 | 14.6 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 106 | 146 |

| Property | MOBILGARD DEO 30 | MOBILGARD DEO 40 |
|--|------------------|------------------|
| Pour Point, °C, ASTM D97 | -21 | -21 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10.1 | 10.1 |
| Viscosity Index, ASTM D2270 | 99 | 99 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved