



## ExxonMobil Jet Fuel

ExxonMobil Commercial Fuel , Peru

### Product Description

Jet A and Jet A-1 are kerosene-type fuels. The primary difference between the two is freeze point, the temperature at which wax crystals disappear in a laboratory test.

Jet A, which is mainly used in the United States, must have a freeze point of minus 40°C or below and does not typically contain static dissipator additive. Jet A-1 must have a freeze point of minus 47°C or below and for locations outside the United States, this fuel normally contains static dissipator additive. There are other key differences between the manufacturing specification within the United States and Europe/Africa/Middle East/Australasia.

ExxonMobil Jet A and ExxonMobil Jet A-1 meet the requirements of ASTM D1655 Standard Specification for Aviation Turbine Fuels. ExxonMobil Jet A-1 also complies with U.K. DEF STAN 91-091, and the JIG (Joint Inspection Group) Aviation Fuel Requirements for Jointly Operated Systems (Check List). Jet A-1 manufactured to Def. Stan. 91-091 has a lower max limit for acidity and additional requirement for conductivity. In all cases, the most recent issue of relevant specifications applies to the product supplied.

### Specifications

| ExxonMobil Jet Fuel meets the following industry specifications: | ExxonMobil Jet A | ExxonMobil Jet A-1 |
|--|------------------|--------------------|
| ASTM D1655   | X                | X                  |
| CGSB 3.23  | X                | X                  |
| U.K. DEF STAN 91-091   |                  | X                  |

Product Properties ASTM D1655, CGSB 3.23, and Def. Stan 91-091

Note: where the required significant figures differ between specs, the larger amount of significant figures is shown below

|                                   | Jet A      | Jet A-1                                    |
|-----------------------------------|------------|--|
| Acidity, mg KOH/g                 | 0.10 Max.  | 0.10 Max. (0.015 Max for Def. Stan 91-091) |
| Aromatics, Vol. %                 | 25 Max.    | 25.0 Max.                                  |
| Sulphur, mercaptan, Wt. %         | 0.003 Max. | 0.0030 Max.                                |
| Sulphur, total, Wt. %             | 0.30 Max.  | 0.30 Max.                                  |
| 10% Distillation, °C              | 205 Max.   | 205.0 Max.                                 |
| Final Boiling Point, °C           | 300 Max.   | 300.0 Max.                                 |
| Distillation Residue, %           | 1.5 Max.   | 1.5 Max.                                   |
| Distillation Loss, %              | 1.5 Max.   | 1.5 Max.                                   |
| Flash Point, °C                   | 38 Min.    | 38.0 Min.                                  |
| Density @ 15°C, kg/m <sup>3</sup> | 775 to 840 | 775.0 to 840.0                             |
| Freeze Point, °C                  | -40 Max    | -47.0 Max                                  |

|  | Jet A                                   | Jet A-1                                 |
|--|---|---|
| Viscosity @ -20°C, mm/s  | 8.0 Max.                                | 8.000 Max.                              |
| Net Heat of Combustion, MJ/kg  | 42.8 Min.                               | 42.80 Min.                              |
| One of the following shall be met:   |   |   |
| 1) Smoke Point, mm, or   | 25.0 Min.                               | 25.0 Min.                               |
| 2) Smoke Point, mm, and  | 18.0 Min.                               | 18.0 Min.                               |
| Naphthalenes, Vol. %   | 3.0 Max                                 | 3.00 Max.                               |
| Copper Strip Corrosion, 2 h % 100°C  | No. 1 Max.                              | No. 1 Max.                              |
| Thermal Stability @ 260°C:   |   |   |
| -Filter pressure drop, mm Hg   | 25 Max.                                 | 25 Max.                                 |
| -Tube Deposits   | < 3 Max. No Peacock (P) or Abnormal (A) | < 3 Max. No Peacock (P) or Abnormal (A) |
| Existent Gum, mg/100 mL.   | 7 Max.                                  | 7 Max.                                  |
| MSEP Rating  |   |   |
| -Without electrical conductivity additive  | 85                                      | 85                                      |
| -With electrical conductivity additive   | 70                                      | 70                                      |
| Electrical conductivity, pS/m  |   |   |
| *Use of conductivity improver additive and resulting limits are optional in ASTM D1655 | 50 Min. 600 Max.*                       | 50 Min. 600 Max.*                       |

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2022

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,


Torre Real Piso 14 San Isidro

Lima Perú

800 662-4592

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved